CLAMP 212

SKU: 2120000

Bridge clamp for externally corrugated spiral hoses, quick and easy to fit, reusable.



Material and colour

Material body

· stainless steel (1.4016)

Material band clamps

· Stainless steel (1.4301)

Material screw

· Galvanised steel

Material bridge

· Stainless steel (1.4301)

Durability and standards

Standards

· REACH (EG 1907/2006), RoHS

Other

Suitable for hose

· AIRDUC®: 341 + 345 + 363; 350 (AS/ FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT-PUR); 351 + 355 EC; 352 SE RAILWAY; 355 AS; 362 (FOOD / EC) PROTAPE®: 330 (FOOD / BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321 + 326 + 327 + 332; 322 EC, CP, TIMBERDUC®: 531 + 532 + 533 + 534

All information in this technical data sheet has been carefully checked; however, no warranty or liability can be accepted for the accuracy, completeness or up-to-dateness of the information provided. Positive pressure and vacuum are operating limit values at 20 °C. The bending radius is measured on the inside of the hose bend. Subject to technical changes.

CLAMP 212

SKU: 2120000

For hose internal diameter (Min/Max) [mm]	Weight [kg]	Article Number
13 – 16	0.01	21200090000
15 – 18	0.01	21200130000
18 – 26	0.01	21200170000
22 – 28	0.01	21200200000
25 – 29	0.02	21200220000
30 – 35	0.02	21200270000
32 – 37	0.02	21200290000
38 – 44	0.03	21200350000
38 – 45	0.03	21200352002
45 – 50	0.03	21200400000
50 – 55	0.03	21200450000
50 – 55	0.03	21200452002
60 – 65	0.03	21200550000
60 – 65	0.03	21200552002
70 – 75	0.04	21200650000
80 – 85	0.04	21200750000
90 – 95	0.04	21200850000
100 – 105	0.04	21200950000
110 – 115	0.04	21201050000
120 – 125	0.05	21201150000
130 – 135	0.05	21201250000
140 – 145	0.05	21201350000
150 – 155	0.05	21201450000
160 – 165	0.05	21201550000
170 – 175	0.06	21201650000
180 – 185	0.06	21201750000
190 – 195	0.06	21201850000
200 – 205	0.06	21201950000
210 – 215	0.07	21202050000
220 – 225	0.07	21202150000
240 – 245	0.1	21202350000
250 – 255	0.1	21202450000
260 – 265	0.08	21202550000
270 – 275	0.08	21202650000
280 – 285	0.08	21202750000
300 – 305	0.08	21202950000
310 – 315	0.09	21203050000
320 – 325	0.09	21203150000
350 – 355	0.09	21203450000
370 – 375	0.1	21203650000
400 – 405	0.1	21203950000
430 – 435	0.11	21204250000

All information in this technical data sheet has been carefully checked; however, no warranty or liability can be accepted for the accuracy, completeness or up-to-dateness of the information provided. Positive pressure and vacuum are operating limit values at 20 °C. The bending radius is measured on the inside of the hose bend. Subject to technical changes.

CLAMP 212

SKU: 2120000

For hose internal diameter (Min/Max) [mm]	Weight [kg]	Article Number
435 – 450	0.11	21204350000
450 – 455	0.11	21204450000
470 – 475	0.12	21204650000
500 – 505	0.12	21204950000
510 – 535	0.08	21205050000
550 – 575	0.08	21205450000
580 – 605	0.08	21205750000
600 – 625	0.08	21205950000
630 – 655	0.09	21206250000
700 – 725	0.09	21206950000
800 – 825	0.1	21207950000
900 – 925	0.11	21208950000
990 – 1015	0.1	21209850000

All information in this technical data sheet has been carefully checked; however, no warranty or liability can be accepted for the accuracy, completeness or up-to-dateness of the information provided. Positive pressure and vacuum are operating limit values at 20 °C. The bending radius is measured on the inside of the hose bend. Subject to technical changes.