

CLAMP 213

SKU: 2130000

Bridge clamp with quick-release closure for externally corrugated spiral hoses, quick and easy to fit, reusable.



Durability and standards

Standards:

REACH according to --> Technology /
Technical Information / REACH

conforms to RoHS guideline

Clamping range min.	Clamping range max.	Max. production length	Weight	Article Number
[mm]	[mm]	[m]	[kg]	
50 mm	55 mm	0 m	0.08 kg	21300500000
60 mm	65 mm	0 m	0.08 kg	21300600000
65 mm	70 mm	0 m	0.08 kg	21300650000
70 mm	75 mm	0 m	0.08 kg	21300700000
75 mm	80 mm	0 m	0.09 kg	21300750000
80 mm	85 mm	0 m	0.09 kg	21300800000
90 mm	95 mm	0 m	0.09 kg	21300900000
100 mm	105 mm	0 m	0.1 kg	21301000000
110 mm	115 mm	0 m	0.1 kg	21301100000
115 mm	120 mm	0 m	0.1 kg	21301150000
120 mm	125 mm	0 m	0.1 kg	21301200000
125 mm	130 mm	0 m	0.1 kg	21301250000
130 mm	135 mm	0 m	0.11 kg	21301300000
140 mm	145 mm	0 m	0.11 kg	21301400000
150 mm	155 mm	0 m	0.11 kg	21301500000
160 mm	165 mm	0 m	0.12 kg	21301600000
175 mm	180 mm	0 m	0.12 kg	21301750000
180 mm	185 mm	0 m	0.12 kg	21301800000
200 mm	205 mm	0 m	0.13 kg	21302000000
225 mm	230 mm	0 m	0.14 kg	21302250000
250 mm	255 mm	0 m	0.14 kg	21302500000
300 mm	305 mm	0 m	0.16 kg	21303000000
320 mm	325 mm	0 m	0.17 kg	21303200000
400 mm	405 mm	0 m	0.19 kg	21304000000