

Safety clamps

SKU: 5560

Bolted safety clamps made of aluminium for assembling of couplings with smooth or combi hose tail and safety collar.



Description

Accessories: Inklusive Inbusschrauben und Muttern

Durability and standards

Standards:
EN 14420-3

Material and colour

Hauptmaterial: Aluminium
Material:
aluminium

Clamping range min.	Clamping range max.	Working pressure	Total wall thickness	Weight	Internal diameter clamp shells	Article Number
[mm]	[mm]	[bar]	[mm]	[kg]	[mm]	
22 mm	24 mm	25 bar	5 mm	0.11 kg	13 mm	5560013005
30 mm	33 mm	25 bar	6 mm	0.14 kg	19 mm	5560019006
34 mm	37 mm	25 bar	5 mm	0.15 kg	25 mm	5560025005
36 mm	39 mm	25 bar	6 mm	0.15 kg	25 mm	5560025006
41 mm	44 mm	25 bar	5 mm	0.14 kg	32 mm	5560032005
43 mm	46 mm	25 bar	6 mm	0.16 kg	32 mm	5560032006
47 mm	50 mm	25 bar	5 mm	0.16 kg	38 mm	5560038005
47 mm	50 mm	25 bar	8 mm	0.17 kg	32 mm	5560032008
50 mm	53 mm	25 bar	6.5 mm	0.19 kg	38 mm	5560038065
53 mm	56 mm	25 bar	7 mm	0.166 kg	40 mm	5560040007
53 mm	56 mm	25 bar	8 mm	0.18 kg	38 mm	5560038008
57 mm	60 mm	25 bar	10 mm	0.18 kg	38 mm	5560038010
58 mm	61 mm	25 bar	10 mm	0.19 kg	40 mm	5560040010
59 mm	62 mm	25 bar	5 mm	0.27 kg	50 mm	5560050005
62 mm	64 mm	25 bar	6 mm	0.26 kg	50 mm	5560050006
63 mm	67 mm	25 bar	8 mm	0.3 kg	50 mm	5560050008
69 mm	71 mm	25 bar	10 mm	0.32 kg	50 mm	5560050010
74 mm	77 mm	25 bar	6 mm	0.44 kg	63 mm	5560063006
78 mm	82 mm	25 bar	8 mm	0.43 kg	63 mm	5560063008
84 mm	87 mm	25 bar	10 mm	0.46 kg	63 mm	5560063010
85 mm	88 mm	25 bar	5 mm	0.46 kg	75 mm	5560075005
87 mm	90 mm	25 bar	6 mm	0.45 kg	75 mm	5560075006
88 mm	93 mm	25 bar	8 mm	0.46 kg	75 mm	5560075008
94 mm	97 mm	25 bar	8 mm	0.46 kg	80 mm	5560080008
94 mm	97 mm	25 bar	10 mm	0.51 kg	75 mm	5560075010
111 mm	115 mm	25 bar	6.5 mm	1.2 kg	100 mm	5560100065
114 mm	119 mm	25 bar	8 mm	1.15 kg	100 mm	5560100008

Overpressure and underpressure are recommended operating limits; products can be subjected to higher loads on request. The bend radius is measured along the inside of the hose bend. Subject to technical changes. All specifications are general guide values and refer to 20 °C. Further technical information: www.norres-baggerman.com.

Safety clamps

SKU: 5560

Clamping range min.	Clamping range max.	Working pressure	Total wall thickness	Weight	Internal diameter clamp shells	Article Number
[mm]	[mm]	[bar]	[mm]	[kg]	[mm]	
118 mm	122 mm	25 bar	10 mm	1.15 kg	100 mm	5560100010
122 mm	126 mm	25 bar	12 mm	1.284 kg	100 mm	5560100012
143 mm	148 mm	25 bar	10 mm	1.92 kg	125 mm	5560125010
168 mm	174 mm	25 bar	10 mm	3.552 kg	150 mm	5560150010
174 mm	180 mm	25 bar	13 mm	3.1 kg	150 mm	5560150013
222 mm	229 mm	25 bar	12 mm	6.558 kg	200 mm	5560200012