Hose clamps system "Pa-Ri"

SKU: 6180

Pa-Ri system: type 1A hose clamp made of stainless steel.



Material and colour

Main Material

· Stainless steel

Material

· Stainless steel (1.4301)

All information in this technical data sheet has been carefully checked; however, no warranty or liability can be accepted for the accuracy, completeness or up-to-dateness of the information provided. Positive pressure and vacuum are operating limit values at 20 °C. The bending radius is measured on the inside of the hose bend. Subject to technical changes.

Hose clamps system "Pa-Ri"

SKU: 6180

Nominal size	Weight [kg]	Band thickness [mm]	Screw dimensions	Article Number
50	0.149	1	Hex socket screw M6 x 45	6180042054
55	0.156	1	Hex socket screw M6 x 45	6180047057
60	0.161	1	Hex socket screw M6 x 45	6180052064
65	0.163	1	Hex socket screw M6 x 45	6180057069
70	0.171	1	Hex socket screw M6 x 45	6180062074
75	0.179	1	Hex socket screw M6 x 45	6180067079
80	0.185	1	Hex socket screw M6 x 45	6180072084
85	0.187	1	Hex socket screw M6 x 45	6180077089
90	0.196	1	Hex socket screw M6 x 45	6180082094
95	0.202	1	Hex socket screw M6 x 45	6180087099
100	0.208	1	Hex socket screw M6 x 45	6180092104
110	0.216	1	Hex socket screw M6 x 45	6180102114
115	0.22	1	Hex socket screw M6 x 45	6180107119
120	0.223	1	Hex socket screw M6 x 45	6180112124
130	0.241	1	Hex socket screw M6 x 45	6180122134
140	0.242	1	Hex socket screw M6 x 45	6180132144
150	0.265	1	Hex socket screw M6 x 45	6180142154
160	0.27	1	Hex socket screw M6 x 45	6180152164
170	0.279	1	Hex socket screw M6 x 45	6180162174
175	0.28	1	Hex socket screw M6 x 45	6180167179
180	0.292	1	Hex socket screw M6 x 45	6180172184
190	0.3	1	Hex socket screw M6 x 45	6180182194
200	0.315	1	Hex socket screw M6 x 45	6180192204
225	0.338	1	Hex socket screw M6 x 45	6180217229
270	0.371	1	Hex socket screw M6 x 45	6180262274

All information in this technical data sheet has been carefully checked; however, no warranty or liability can be accepted for the accuracy, completeness or up-to-dateness of the information provided. Positive pressure and vacuum are operating limit values at 20 °C. The bending radius is measured on the inside of the hose bend. Subject to technical changes.