

CLAMP 208

SKU: 2080000

Hose clamp for light-duty hoses with smooth outer wall, quick and easy to fit, reusable.



Durability and standards

Standards:

REACH according to --> Technology /
Technical Information / REACH

conforms to RoHS guideline

Material and color

Material body: Galvanized steel

Material bridge:

Body: galvanised steel

Screw: galvanized steel

Clamping range min.	Clamping range max.	Max. production length	Weight	Article Number
[mm]	[mm]	[m]	[kg]	
8 mm	12 mm	–	0 kg	20800080000
10 mm	16 mm	0 m	0.02 kg	20800100000
12 mm	20 mm	0 m	0.02 kg	20800120000
16 mm	25 mm	0 m	0.02 kg	20800160000
20 mm	32 mm	0 m	0.02 kg	20800200000
25 mm	40 mm	0 m	0.02 kg	20800250000
32 mm	50 mm	0 m	0.02 kg	20800320000
40 mm	60 mm	0 m	0.03 kg	20800400000
50 mm	70 mm	0 m	0.03 kg	20800500000
60 mm	80 mm	0 m	0.03 kg	20800600000
70 mm	90 mm	0 m	0.03 kg	20800700000
80 mm	100 mm	0 m	0.03 kg	20800800000
90 mm	110 mm	0 m	0.04 kg	20800900000
100 mm	120 mm	0 m	0.04 kg	20801000000
110 mm	130 mm	0 m	0.04 kg	20801100000
120 mm	140 mm	0 m	0.04 kg	20801200000
130 mm	150 mm	0 m	0.04 kg	20801300000
140 mm	160 mm	0 m	0.04 kg	20801400000
150 mm	170 mm	0 m	0.05 kg	20801500000
160 mm	180 mm	0 m	0.05 kg	20801600000
170 mm	190 mm	0 m	0.05 kg	20801700000
180 mm	200 mm	0 m	0.05 kg	20801800000
190 mm	210 mm	0 m	0.06 kg	20801900000
200 mm	220 mm	0 m	0.06 kg	20802000000
210 mm	230 mm	0 m	0.06 kg	20802100000
220 mm	240 mm	0 m	0.06 kg	20802200000
230 mm	250 mm	0 m	0.06 kg	20802300000

Over and under pressure are recommended operating limits, products can be subjected to higher loads on request. The bending radius is measured through the inside of the hose bend. Subject to technical changes. All specifications are general guide values and refer to 20 °C. Further technical information: www.norres-baggerman.com.

CLAMP 208

SKU: 2080000

Clamping range min.	Clamping range max.	Max. production length	Weight	Article Number
[mm]	[mm]	[m]	[kg]	
240 mm	260 mm	0 m	0.07 kg	20802400000
250 mm	270 mm	0 m	0.07 kg	20802500000
260 mm	280 mm	0 m	0.07 kg	20802600000
270 mm	290 mm	0 m	0.07 kg	20802700000
280 mm	300 mm	0 m	0.07 kg	20802800000
290 mm	310 mm	0 m	0.07 kg	20802900000
300 mm	320 mm	0 m	0.08 kg	20803000000
310 mm	330 mm	0 m	0.08 kg	20803100000
320 mm	340 mm	0 m	0.08 kg	20803200000
330 mm	350 mm	0 m	0.08 kg	20803300000
340 mm	360 mm	0 m	0.09 kg	20803400000
350 mm	370 mm	0 m	0.09 kg	20803500000
360 mm	380 mm	0 m	0.09 kg	20803600000
370 mm	390 mm	0 m	0.09 kg	20803700000
380 mm	400 mm	0 m	0.09 kg	20803800000
400 mm	420 mm	0 m	0.1 kg	20804000000
420 mm	440 mm	0 m	0.1 kg	20804200000
440 mm	460 mm	0 m	0.11 kg	20804400000
450 mm	470 mm	0 m	0.11 kg	20804500000
460 mm	480 mm	0 m	0.11 kg	20804600000
480 mm	500 mm	0 m	0.11 kg	20804800000
500 mm	520 mm	0 m	0.12 kg	20805000000

Over and under pressure are recommended operating limits, products can be subjected to higher loads on request. The bending radius is measured through the inside of the hose bend. Subject to technical changes. All specifications are general guide values and refer to 20 °C. Further technical information: www.norres-baggerman.com.