

CLAMP 208

SKU: 2089230

Hose clamp for light-duty hoses with smooth outer wall, quick and easy to fit, reusable.



Durability and standards

Standards:

REACH according to --> Technology /
Technical Information / REACH

conforms to RoHS guideline

Material and color

Material body: Stainless steel (1.4016)

Material bridge:

material body: stainless steel 1.4301 = AISI
304

Stainless steel screw 1.4301 = AISI 304

Clamping range min.	Clamping range max.	Max. production length	Weight	Article Number
[mm]	[mm]	[m]	[kg]	
8 mm	12 mm	0 m	0.02 kg	20800089230
10 mm	16 mm	0 m	0.02 kg	20800109230
12 mm	20 mm	0 m	0.02 kg	20800129230
16 mm	25 mm	0 m	0.02 kg	20800169230
20 mm	32 mm	0 m	0.02 kg	20800209230
25 mm	40 mm	0 m	0.02 kg	20800259230
32 mm	50 mm	0 m	0.02 kg	20800329230
40 mm	60 mm	0 m	0.03 kg	20800409230
50 mm	70 mm	0 m	0.03 kg	20800509230
70 mm	90 mm	0 m	0.03 kg	20800709230
80 mm	100 mm	0 m	0.03 kg	20800809230
90 mm	110 mm	0 m	0.04 kg	20800909230
110 mm	130 mm	0 m	0.04 kg	20801109230
130 mm	150 mm	0 m	0.04 kg	20801309230
150 mm	170 mm	0 m	0.05 kg	20801509230
160 mm	180 mm	0 m	0.05 kg	20801609230
200 mm	220 mm	0 m	0.06 kg	20802009230
210 mm	230 mm	0 m	0.06 kg	20802109230
220 mm	240 mm	0 m	0.06 kg	20802209230
230 mm	250 mm	0 m	0.06 kg	20802309230
240 mm	260 mm	0 m	0.07 kg	20802409230
250 mm	270 mm	0 m	0.07 kg	20802509230
260 mm	280 mm	0 m	0.07 kg	20802609230
270 mm	290 mm	0 m	0.07 kg	20802709230
290 mm	310 mm	0 m	0.07 kg	20802909230
300 mm	320 mm	0 m	0.08 kg	20803009230
310 mm	330 mm	0 m	0.08 kg	20803109230

Over and under pressure are recommended operating limits, products can be subjected to higher loads on request. The bending radius is measured through the inside of the hose bend. Subject to technical changes. All specifications are general guide values and refer to 20 °C. Further technical information: www.norres-baggerman.com.

CLAMP 208

SKU: 2089230

Clamping range min.	Clamping range max.	Max. production length	Weight	Article Number
[mm]	[mm]	[m]	[kg]	
320 mm	340 mm	0 m	0.08 kg	20803209230
330 mm	350 mm	0 m	0.08 kg	20803309230
340 mm	360 mm	0 m	0.09 kg	20803409230
350 mm	370 mm	0 m	0.09 kg	20803509230
360 mm	380 mm	0 m	0.09 kg	20803609230
370 mm	390 mm	0 m	0.09 kg	20803709230
380 mm	400 mm	0 m	0.09 kg	20803809230
400 mm	420 mm	0 m	0.1 kg	20804009230
420 mm	440 mm	0 m	0.1 kg	20804209230
440 mm	460 mm	0 m	0.11 kg	20804409230
460 mm	480 mm	0 m	0.11 kg	20804609230
480 mm	500 mm	0 m	0.11 kg	20804809230