CLAMP 212 EC

SKU: 2122878

Bridge clamp with integral grounding for externally corrugated spiral hoses, quick and easy to fit, reusable.



Material and color

Material body

· stainless steel (1.4016)

Material bridge

· Stainless steel (1.4301)

Durability and standards

Standards

· REACH (EG 1907/2006), RoHS

Other

Suitable for hose

· AIRDUC®: 341 + 345 + 363; 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC); TIMBERDUC®: 533 AS

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.

CLAMP 212 EC

SKU: 2122878

For hose internal diameter (Min/Max) [mm]	Weight [kg]	Article Number
30 – 35	0.04	21200272878
38 – 45	0.05	21200352878
50 – 55	0.05	21200452878
60 – 65	0.05	21200552878
70 – 75	0.06	21200652878
80 – 85	0.06	21200752878
90 – 95	0.06	21200852878
100 – 105	0.07	21200952878
110 – 115	0.07	21201052878
120 – 127	0.07	21201152878
130 – 135	0.07	21201252878
140 – 145	0.07	21201352878
150 – 155	0.08	21201452878
160 – 165	0.08	21201552878
170 – 175	1.06	21201652878
180 – 185	0.06	21201752878
190 – 195	0.08	21201852878
200 – 205	0.09	21201952878
210 – 215	0.07	21202052878
250 – 255	0.13	21202452878
300 – 305	0.11	21202952878
320 – 325	0.09	21203152878
350 – 355	0.12	21203452878
400 – 405	0.13	21203952878
500 – 505	0.13	21204952878

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.