CLAMP 213

SKU: 2130000

Bridge clamp with quick-release closure for externally corrugated spiral hoses, quick and easy to fit, reusable.



Material and color

Material body

· stainless steel (1.4016)

Material screw

· Stainless steel (1.4301)

Durability and standards

Standards

· REACH (EG 1907/2006), RoHS

Other

Suitable for hose

· AIRDUC®: 341 + 345 + 363; 350 (AS /FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC); PROTAPE®: 326 + 327 MEMORY; 330 (FOOD / AS BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321; 322 EC; 332 SE; CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC); TIMBERDUC®: 531 - 533 AS

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.

CLAMP 213

SKU: 2130000

For hose internal diameter [mm]	Weight [kg]	Article Number
50	0.08	21300500000
60	0.08	21300600000
65	0.08	21300650000
70	0.08	21300700000
75	0.09	21300750000
80	0.09	21300800000
90	0.09	21300900000
100	0.1	21301000000
110	0.1	21301100000
115	0.1	21301150000
120	0.1	21301200000
125	0.1	21301250000
130	0.11	21301300000
140	0.11	21301400000
150	0.11	21301500000
160	0.12	21301600000
175	0.12	21301750000
180	0.12	21301800000
200	0.13	21302000000
225	0.14	21302250000
250	0.14	21302500000
300	0.16	21303000000
320	0.17	21303200000
400	0.19	21304000000

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.