

CLAMP 216

SKU: 2160000

Hose clamp for watertight attachment of heavy, externally corrugated spiral hoses, quick and easy to fit, reusable.



Durability and standards

Standards:

REACH according to --> Technology /
Technical Information / REACH
conforms to RoHS guideline

Material and color

Material body: Stainless steel (1.4016)

Material screw: steel, chromated

For hose internal diameter	Max. production length	Weight	Article Number
[mm]	[m]	[kg]	
42 mm	0 m	0.03 kg	21600420000
48 mm	0 m	0.03 kg	21600480000
50 mm	0 m	0.04 kg	21600500000
65 mm	0 m	0.04 kg	21600650000
76 mm	0 m	0.04 kg	21600760000
55 mm	0 m	0.04 kg	21600550000
60 mm	0 m	0.04 kg	21600600000
70 mm	0 m	0.04 kg	21600700000
75 mm	0 m	0.04 kg	21600750000
80 mm	0 m	0.04 kg	21600800000
125 mm	0 m	0.05 kg	21601250000
140 mm	0 m	0.05 kg	21601400000
90 mm	0 m	0.05 kg	21600900000
100 mm	0 m	0.05 kg	21601000000
102 mm	0 m	0.05 kg	21601020000
110 mm	0 m	0.05 kg	21601100000
115 mm	0 m	0.05 kg	21601150000
120 mm	0 m	0.05 kg	21601200000
127 mm	0 m	0.05 kg	21601270000
130 mm	0 m	0.06 kg	21601300000
150 mm	0 m	0.06 kg	21601500000
152 mm	0 m	0.06 kg	21601520000
160 mm	0 m	0.06 kg	21601600000
170 mm	0 m	0.06 kg	21601700000
200 mm	0 m	0.07 kg	21602000000
175 mm	0 m	0.07 kg	21601750000
180 mm	0 m	0.07 kg	21601800000
225 mm	0 m	0.08 kg	21602250000

Over and under pressure are recommended operating limits, products can be subjected to higher loads on request. The bending radius is measured through the inside of the hose bend. Subject to technical changes. All specifications are general guide values and refer to 20 °C. Further technical information: www.norres-baggerman.com.

CLAMP 216

SKU: 2160000

For hose internal diameter	Max. production length	Weight	Article Number
[mm]	[m]	[kg]	
250 mm	0 m	0.08 kg	21602500000
300 mm	0 m	0.1 kg	21603000000
400 mm	0 m	0.12 kg	21604000000