

TEMPERFORM/BLUE

SKU: 3128

Extremely flexible cooling water hose, buckling resistant, resistant to high and low temperatures, ideal for temperature control applications in injection moulding technology. Blue construction cover.





Technical specifications

Medium

· Gas, Dust, Liquid, Solid

Areas of application

Applications

· Aluminum smelters, Coating systems, Municipal vehicles, Water hose, Hot water operation, Cooling water, Injection moulding machines, Tunnel construction

Industries

· Paper industry, Textile industry, Agricultural industry, Construction industry, Plastics industry, Mechanical engineering, Municipal technology, Cleaning machine industry, Environmental and cleaning technology, Surface technology, Automation industry, Metal industry, Mining industry

Pressure and temperature

Temperature normal range (min/max)

· -20 °C – 100 °C

Material and color

Color of inner tube core

· black

Color of outer cover

· Blue

Material outer cover

· EPDM

Material inner tube

· EPDM

Durability and standards

Standards

· EN ISO 1307:2008

Durability outer cover

· Ozone-resistant, UV resistant

Design and production

Construction outer cover

· Smooth

Inserts

· textile plies

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.

TEMPERFORM/BLUE

SKU: 3128

Inner diameter [mm]	Outer diameter [mm]	Working pressure at 20°C [bar]	Burst pressure [bar]	Total wall thickness [mm]	Bending radius [mm]	Max. production length [m]	Weight [kg]	Article Number
9.5	18	20	60	4.65	75	40	0.265	3128009001
12.7	22	20	60	4.65	100	40	0.368	3128013001

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.