
SILOCORD®/SPEZIAL

SKU: 3542

Highly abrasion-resistant silo conveyor hose, ideal for filling and emptying silos of highly abrasive materials such as grit, soda or quark sand.





Technical specifications

Interior abrasion value

· 70 mm3

Medium

· Solid

Areas of application

Applications

· Suction trucks, Silo trucks, Tunnel construction, Cement conveying

Industries

· Chemical industry, Agricultural industry, Construction industry, Horticulture, Pump and compressor industry, Silo and conveying technology industry

Pressure and temperature

Temperature normal range (min/max)

· -30 °C – 85 °C

Electrical properties

Electrical resistance of cover

· Electrically conductive <10^6 Ω

Electrical resistance of core

· Electrically conductive <10^6 Ω

Material and color

Material wire

· Copper

Color of inner tube core

· black

Color of outer cover

· black

Material outer cover

· NR/SBR

Material inner tube

· NR

Durability and standards

Standards

· ISO 4649 (formerly DIN 53516), EN ISO 1307:2008

Design and production

Construction outer cover

· Wrapped

Inserts

· textile plies

Inner tube

· Smooth

Description

Imprint

· Silocord® / Spezial für Splitt - Soda - Quarzsand PN 10 bar - M

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.

SILOCORD®/SPEZIAL

SKU: 3542

Inner diameter [mm]	Outer diameter [mm]	Working pressure [bar]	Burst pressure [bar]	Total wall thickness [mm]	Bending radius [mm]	Max. production length [m]	Weight [kg]	Article Number
76	98	10	30	11	760	40	3.44	3542076098
102	126	10	30	12	1.02	20	4.85	3542102126

All information in this technical data sheet has been carefully reviewed; however, no warranty or liability can be accepted for the accuracy, completeness, or currentness of the information provided. Positive pressure and vacuum are operating limit values at 68 °F (20 °C). The bend radius is measured on the inside of the hose bend. Subject to technical changes.