



NORRES
BAGGERMAN

Better. Stronger. Together.

Selection. Quality. Reliability.
Hose systems for
the agricultural industry.



We provide innovative solutions. You get reliability and efficiency.

In modern agriculture, efficiency is crucial. Reliable hose systems are vital in almost all applications. They ensure the optimal distribution of water, liquid manure, pesticides, seeds, dairy products and fertilizers, ensuring the smooth operation of machines and equipment.

Given the extreme natural and mechanical stresses that these systems are subjected, high durability and rapid replacement are critical to minimizing downtime during critical seasons such as planting and harvesting.

Our hose systems meet the demanding requirements of agriculture:

- **High tensile strength:** Essential for preventing cracks and breaks, it increases resistance to wear and extends the life of the hose.
- **Robustness:** To withstand extreme loads without sacrificing flexibility, hoses must be designed to be particularly robust.
- **Optimal flow:** For planting, a high flow rate is crucial to ensure precise and even distribution of seed.
- **High abrasion resistance:** Protects against rapid wear due to friction, which is especially important when spreading manure or fertilizer.

Whether for planting, fertilizing, spraying or irrigation – we offer the right hose for every agricultural application, including the right couplings and accessories. Our products are known for high tensile strength, tear and abrasion resistance, UV and microbial resistance, as well as kink stability and elasticity.

Our product range includes smooth and spiral hoses with and without fabric inserts made of PVC, PU and rubber. This variety of materials, allows us to meet all

agricultural requirements, while setting the standards in terms of quality and innovation.

Investing in long-lasting hose systems pays off, by sustainably increasing the efficiency and productivity of farms while protecting the environment by using resources more effectively and reducing waste.



NORRES Baggerman

The merger of NORRES and Baggerman has resulted in the creation of NORRES Baggerman – a global market leader and manufacturer of industrial hose systems.

PAGE 04



Planting and fertilization (solids)

Seed and solid fertilizer hoses from NORRES Baggerman are a reliable solution for the precise and efficient application of seeds and solid fertilizers.

PAGE 06



Manure

Our wide range of slurry hoses enables us to cover a range of applications, including yours.

PAGE 08



Irrigation

Our temperature-resistant irrigation hoses ensure efficient irrigation while conserving resources at the same time.

PAGE 10



Biogas

With the pressure-resistant, antistatic and high-density hoses from NORRES Baggerman, you can always operate your biogas plant safely.

PAGE 12



Fertilization & Crop Protection (liquid)

The chemical-resistant and UV-stable hoses from NORRES Baggerman ensure reliable and precise distribution of liquid fertilizers and plant protection products.

PAGE 14



General Agricultural Machinery

We also offer the right solutions for other related, such as oil, compressed air, brake and coolant hoses

PAGE 15



Connection technology

We offer a complete range of coupling and connection systems for all common hose types.

PAGE 16

You expect performance and a variety of materials. We have both. And more.

The merger of NORRES in Gelsenkirchen and Baggerman in Roermond has resulted in the creation of NORRES Baggerman – a global market leader in the manufacture and technical installation of industrial hose systems. Our unique portfolio is characterized by a variety of materials and application expertise. In our worldwide competence centers, we develop and have a wide range of PVC, PU and rubber hoses, as well as suitable couplings and accessories. As a result, we can meet virtually any requirement for a wide variety of applications.

Millions of kilometers of NORRES Baggerman hoses are already successfully used in agriculture, the food and pharmaceutical industries, the plastics and wood processing industries, as well as in robotics, fluid technology, energy technology and mechanical and plant engineering.

We are deeply rooted in our region and its people. Worldwide, we employ more than 400 people at six production sites in Germany, Italy, Switzerland, North America and China as well as at 14 sales, service and warehouse locations.

Certified quality and service worldwide.

Our customers benefit from consistently high and reliable global quality, flexible service and fast response times – both for original equipment and for part replacement. In addition, the quality of our production convinces both partners and customers worldwide. As a certified manufacturer according to DIN ISO 9001, we guarantee the highest quality standards. Our products comply with all relevant regulations.

Better. Stronger. Together.

We stand for strong commitment and innovative strength, which we use for the benefit of our customers.

Better.

Our customers benefit from our expertise in a variety of materials and applications, the highest quality standards, many years of experience and excellent service. We strive for continuous improvement.

Stronger.

With production and service centers around the world, we are a reliable partner for globally active companies. We guarantee short delivery and response times.

Together.

Thanks to our combined expertise, we offer our customers outstanding and innovative solutions – because we are more successful together.



A good harvest starts with quality planting. And the right hoses for the job.


Only precise and efficient seed distribution will lead to uniform seeding and plant growth. And for an even application of seeds, optimal and constant flow is particularly important.

Therefore, the requirements of hose systems for sowing are very high. They must not only be durable, UV-resistant and antistatic, but also micro- and hydrolysis-resistant, abrasion-resistant, flow-optimized and highly flexible.


Seed and solid fertilizer hoses from NORRES Baggerman are a reliable solution for the precise and efficient application of seeds and fertilizers. Thanks to the high-quality materials and tight production standards, they guarantee optimal performance and durability.



Medium



Properties



Product	PROTAPE® PUR 330 FOOD (LD)	PROTAPE® PUR-C 335 FOOD-AS FLAT	AIRDUC® PUR 350 FOOD-AS (MD)	AIRDUC® PUR 351 FOOD (MD)
Medium				
Properties				
Applications	Suction hose for air and dust	For hoppers and condensers	Transport of seeds and solid fertilizers	Transport of seeds, cereals and solid fertilizers
UV/weather protection	++	++	++	++
Throughput	+++	+	+++	+++
Flexibility	++++	++++	+++	++
Robustness	+	+	++	+++
Cold flexibility	++++	++++	++++	++++
Abrasion	+	+	++	+++
Available inner diameters (in mm)	25-450	50-405	25-450	25-500
Material	PU Premium polyurethane, smooth inside/corrugated outside, steel spiral	PU Premium polyurethane, smooth inside/outside	PU Premium polyurethane, smooth inside/corrugated outside, steel spiral	PU Premium polyurethane, smooth inside/corrugated outside, steel spiral
Bend	0,6 x Inner Diameter	-	0,7 x Inner Diameter	1 x Inner Diameter
Temperature	-40°C to +90°C short time up to +125°C	-40°C to +90°C short time up to +125°C	-40°C to +90°C short time up to +125°C	-40°C to +90°C short time up to +125°C
Vacuum	variable depending on diameter	-	variable depending on diameter	variable depending on diameter
More Benefits	Compressable	Vibration resistant, antistatic	Antistatic	-

Product	AIRDUC® PUR 355 FOOD (HD)	NORPLAST® PVC COSMO® ELASTICO SEEDER	NORPLAST® PVC COSMO® ELASTICO SEEDER PU INLINER	NORPLAST® PUR 385 AIRFLEX® PU FOOD
Medium				
Properties				
Applications	High-throughput for feed and grain handling	Feed hose for seeds and solid fertilizers	Feed hose for seeds and solid fertilizers	Extraction and conveying of foodstuffs
UV/weather protection	++	+++	+++	++
Throughput	+++	+++	+++	+++
Flexibility	++	+++	++	+++
Robustness	++++	+++	+++	+
Cold flexibility	++++	+	+	++++
Abrasion	++++	+	+++	+++
Available inner diameters (in mm)	13-300	30-32	30-32	25-203
Material	PU Premium polyurethane, smooth inside/corrugated outside, steel spiral	PVC smooth inside/outside, rigid PVC spiral	PU-Inliners with PVC outer cover, smooth inside/outside, rigid PVC spiral	PU Premium polyurethane, very smooth on the inside/corrugated on the outside, rigid PVC spiral
Bend	1 x Inner Diameter	4 x Inner Diameter	4 x Inner Diameter	1 x Inner Diameter
Temperature	-40°C to +90°C short time up to +125°C	-15°C to +60°C	-15°C to +60°C	-25°C to +85°C
Vacuum	variable depending on diameter	0,6 bar	0,7 bar	variable depending on diameter
More Benefits	High compressive and vacuum resistance	Extremely kink-resistant	Mirror-smooth PU inner lining	Mirror-smooth on the inside, even in the bend

Durable, buckling-resistant manure hoses.

We have the right solution.


The application of liquid manure requires reliable and precise technology. Hose systems must be able to withstand the harsh operating conditions and ensure reliable and constant distribution.

Manure hoses from NORRES Baggerman meet all the technical requirements that are crucial in suction, pressure or drain hoses, as well as in drag and distribution hoses. These include tensile strength, kink stability, UV, weather and microbe protection, as well as flexibility and tear resistance.

With their robust construction and long-lasting materials, slurry hoses from NORRES Baggerman are a reliable solution for the agricultural industry. With our portfolio of slurry hoses, we cover a wide range of applications, including yours.




Medium



Gas Dust Liquid Solid

Properties



Product	NORPLAST® PVC 379 COSMO® ELASTICO	COSMO®/RIGIDO	NORPLAST® PVC 389 SUPERELASTICO	Deltaflex®
Medium				
Properties				
Applications	Manure dribble hose	Rigid dribble hose end piece for manure dosing at the outlet	Slurry tanker filling, slurry distribution, filling	Slurry distribution and filling even with tight bends
UV/weather protection	++	++	++	+
Throughput	+++	+++	+++	++
Flexibility	+++	+++	+++	++
Robustness	++	++	++	+++
Cold flexibility	++	++	+++	++
Available diameters (in mm)	40-51	40-51	25-203	50-203
Material	PVC smooth inside/outside, rigid PVC spiral	PVC smooth inside/outside, rigid PVC spiral	PVC smooth on the inside/slightly corrugated on the outside, hollow rigid PVC spiral	Rubber (SBR) smooth inside/corrugated outside, steel spiral and fabric inserts
Bend	4 x Inner Diameter	-	3.5 x Inner Diameter	3.5 x Inner Diameter
Temperature	-15°C to +60°C	-15°C to +60°C	-25°C to +60°C	-30°C to +85°C
Vacuum	0,6 bar	0,6 bar	0,9 bar	0,9 bar
Working pressure	-	-	1,5-7 bar (depending on diameter)	3 bar
More Benefits	High tensile strength up to 1,600 N	Straight fixed lengths, no pre-curvature from the roll	Lightweight for comfortable handling	Wide range of prefabricated fixed lengths

Product	HEDUFLEX®/GRECATO	ARMOFLEX®	NORPLAST® PVC 389 NAFTOIL BUNA	Connection
Medium				
Properties				
Applications	Slurry distribution and filling	Trailing shoe application, even around tight bends	Slurry distribution even at extremely low temperatures	
UV/weather protection	++	+++	++	
Throughput	++	+++	+++	
Flexibility	++	+++	++	
Robustness	+++	++	+	
Cold flexibility	+++	++	+++	
Available diameters (in mm)	76-203	10-152	25-152	
Material	Rubber (SBR) smooth on the inside/corrugated on the outside, steel spiral, fabric inserts	PVC inside/outside smooth, with steel spiral	NBR/PVC smooth inside/slightly corrugated outside, hollow rigid PVC spiral	
Bend	4 x Inner Diameter	3x Inner Diameter	3 x Inner Diameter	
Temperature	-30°C to +85°C	-15°C to +60°C	-30°C to +65°C	
Vacuum	0,9 bar	0,9 bar	0,9 bar	
Working pressure	6 bar	variable per diameter	variable per diameter	
More Benefits	Highly wear-resistant	-	Hollow spiral for lower axle load and more slurry in the tank (from DN 63), oil-resistant, lightweight	

Efficient irrigation increases yields. And conserves water resources with the right hose.

Efficient irrigation of agricultural land and greenhouses is becoming increasingly important in the face of a changing climate. Effective and sustainable use of water is essential to avoid yield and quality losses over time.

Reliable hose systems play a crucial role in this. The irrigation hoses from NORRES Baggerman are robust and reliable suitable for a range of irrigation systems.

They enable efficient use of resources and maximize yields and quality, even under challenging conditions. At the same time, they meet important criteria such as flexibility, durability, ease of maintenance as well as temperature and UV resistance.



Medium

- Gas
- Dust
- Liquid
- Solid

Properties

- Abrasion resistant
- PRE-PUR®
- treadable/traversable
- Internal Smoothness
- Partially coloured
- Highly flexible
- Microbe-resistant
- Food-safe
- Flame retardant
- Antistatic/Conductive
- Torsion-free
- Pressure resistant
- Dimensionally stable
- Flexible at low temperatures
- Oil resistant

Product	TRICOTECH®	CALORFORM	EUROLON®	AGRIFLAT
Medium				
Properties				
Applications	Irrigation of greenhouses	Irrigation and cleaning in stables	Irrigation of fields and horticulture	Irrigation of fields and horticulture
UV/weather protection	++	+++	++	+++
Throughput		+++	+++	+++
Flexibility	++	+++	+	+
Robustness	++	+++	++	+++
Cold flexibility	+	+++	+	++
Abrasion	-	-	-	-
Available inner diameters (in mm)	12,5-50	10-25	25-203	19-203
Material	PVC smooth inside/outside, textile inlay	Rubber (EPDM) smooth inside/outside, textile inlay	PVC smooth inside/outside, textile inlay	Rubber (NBR/PVC) smooth inside/outside with longitudinal protective ribs, textile insert
Bend	approx. 8 x inner diameter	approx. 6 x inner diameter	-	-
Temperature	-10°C to +60°C	-40°C to +95°C	-20°C to +60°C	-20°C to +80°C
Vacuum	-	-	-	-
Working pressure	10 bar	20 bar	4-7 bar (depending on diameter)	10-25 bar (depending on diameter)
More Benefits	Torsion-free due to special design inside	Particularly flexible even in cold temperatures	Single-use extrusion for a longer service life, can be rolled up flat	Abrasion-resistant on the outside due to longitudinal protection ribs

Product	COSMO®	ARMOFLEX®	INDUCORD®	HEDUFLEX®
Medium				
Properties				
Applications	Drainage of water, suction hose in well construction	Water supply and drainage	Water hose for high demands in agriculture	Water hose for high demands in agriculture for suction and pressure applications
UV/weather protection	++	+++	++	++
Throughput	+++	+++	++	+++
Flexibility	++	+++	++	+++
Robustness	+	++	++	+++
Cold flexibility	+	++	++	+++
Abrasion		+		
Available inner diameters (in mm)	20-102	10-152	22-254	19-305
Material	PVC smooth on the inside/slightly wavy on the outside, rigid PVC spiral	PVC smooth inside and outside with steel spiral	Rubber (SBR) smooth inside/outside, textile inserts	Rubber (SBR) smooth inside/outside with steel spiral and fabric inserts
Bend	approx. 4 x inner diameter	3 x Inner Diameter	approx. 8x ID up to DN 100 approx. 10x ID from DN 100	approx. 5 x inner diameter
Temperature	-15°C to +60°C	-15°C to +60°C	-20°C to +70°C	-30°C to +80°C
Vacuum	0,6 bar	0,9 bar	-	0,9 bar
Working pressure	-	variable depending on diameter	10 bar	10 bar (DN 203/254/305 6 bar)
More Benefits	-	Food	Available in many diameters	Available in many diameters


Create secure energy with biogas. And safety with our hoses.

When selecting and using hoses in biogas plants, several factors must be taken into account to ensure the safety and efficiency of the plant. The passage of gases through hose lines can result in their accumulation in the ambient air and thus lead to the formation of explosive gas-air mixtures.


First and foremost, the hose must be resistant to the media found in the biogas plant, such as biogas, fermentation substrates, condensate and cleaning agents. It must be able to withstand the pressure in the

system, be easy to handle and install, and have a long service life. With the pressure-resistant, antistatic and high-density hoses from NORRES Baggerman, you can always operate your biogas plant safely.

Medium



Properties



Product	PROTAPE® PVC 371 AS (HD)	PROTAPE® TPE 320 AS (XLD)	AIRDUC® TPE 363 (MD)	PROTAPE® PUR 330 AS BLACK (LD)
Medium				
Properties				
Applications	Suction hose for gaseous media	Transport of hot and cold gases, dusts, powders and fibres	Transport of hot and cold gases, dusts, powders and fibres	Transport of hot and cold gases, abrasive dusts, powders and fibres
UV/weather protection	++	+++	+++	++
Throughput				
Flexibility	+++	+++	+	+
Robustness			+	+
Available inner diameters (in mm)	40-508	50-250	30-250	40-203
Material	PVC with steel spiral	TPE with steel spiral	TPE with steel spiral	TPE with steel spiral
Bend	approx. 1 x inner diameter	approx. 0.5 x inner diameter	approx. 0.5 x inner diameter	approx. 0.5 x inner diameter
Temperature	-20°C to +90°C	-40°C to +125°C short-term up to 150°C	-40°C to +125°C short-term up to 150°C	+90°C short-term up to 125°C
Vacuum	variable depending on diameter	variable depending on diameter	variable depending on diameter	variable depending on diameter
Working pressure	-	-	-	-
More Benefits	Compression	Compressible, antistatic	Antistatic	Antistatic


Product	NORPLAST® PVC 389 SUPERELASTICO	AIRDUC® PUR-INOX 355 FOOD-AS (HD)	RADIACORD®/HP	ARIAFORM®/DIN
Medium				
Properties				
Applications	Filling the biogas plant with biomass	Transport of abrasive powders, bulk solids, granules and gases	Clamping profile hose for attaching the biofilm to the roof	Compressed air hose for filling the clamping profile hose
UV/weather protection	++	++	+++	+++
Throughput	+++	++		
Flexibility	+++	++	++	++
Robustness	++	+++	+++	+++
Cold flexibility	+++	+++	+	+
Abrasion		+++		
Available inner diameters (in mm)	25-203	25-203	28	6-25
Material	PVC slightly corrugated on the outside with hollow rigid PVC spiral	PURE smooth on the inside/slightly wavy on the outside, stainless steel spiral	EPDM Smooth inside/outside	TPE Smooth inside/outside, with fabric inserts
Bend	approx. 3.5 x inner diameter	approx. 0.7 x inner diameter	approx. 10 x inner diameter	approx. 8 x inner diameter
Temperature	-25°C to +60°C	up to +90°C for short periods up to 125°C	-40°C to +95°C	-30°C to +50°C
Vacuum	0.9 bar	variable depending on diameter	-	-
Working pressure	1.5 to 7 bar (depending on diameter)	0.6-3.5 bar (depending on dimensions)	10 bar	Air: max. 10 bar Water: max 16 bar
More Benefits	Weight savings due to hollow spiral	Antistatic	-	Age

Fertilizing makes it grow. Our hoses make it flow.


The targeted and effective distribution of liquid fertilizers and pesticides is crucial for healthy plant growth.

Developed to withstand the demanding and tough conditions of everyday agricultural use, the hoses from NORRES Baggerman offer consistently reliable performance. Thanks to their excellent chemical resistance and UV stability, they guarantee long-lasting service life without sacrificing performance. Their remarkable flexibility makes them easy to handle while allowing for smooth application, especially when folding and unfolding booms. In addition, thanks to their kink resistance, our hoses ensure a continuous and trouble-free flow, enabling efficient application of the agents.

Medium



Properties



CALORFORM



Areas of application:

Distribution hose for fertilizers and pesticides on the boom

Properties:

Particularly UV- and weather-resistant | robust design for high demands | suitable for a wide range of pesticides and fertilisers | flexible even at cold ambient temperatures

Material: EPDM

smooth inside/outside, textile insert

Bending radius:

approx. 6x inner diameter


Temperature:

-40°C to +95°C


Operating pressure: 20 bar

Special feature:

Particularly flexible even in cold temperatures



CORRUFLEX/BUNA



Areas of application:

Distribution hose for fertilizers and pesticides under the tank

Properties:

Particularly flexible for the tightest bending radii under the tank. Resistant to a wide range of pesticides and fertilisers

Material: TPE

black inside, blue rigid PVC spiral outside

Bending radius:

approx. 3x inner diameter

Temperature:

-30°C to +65°C

Vacuum: 0.9 bar

Operating pressure: 2 bar

Special feature:

Perfectly smooth on the inside, even in the tightest installation situations, for optimal flow

You have additional applications? We have the right hose.

In addition to the traditional areas of application, hoses also play a central role in other areas of the agricultural industry.

For example, for the operation of silo trucks, trailers and other agricultural vehicles, as well as for the transport of animal feed or dairy products. They must meet high requirements such as temperature and pressure resistance, chemical resistance and food safety standards.

The selection of high-quality hoses is therefore crucial for efficiency and trouble-free operation in the agricultural sector.



AIRBRAKE



Areas of application:

Air pressure brake hose

Properties:

Standardized UV and weather-resistant compressed air hose for air pressure brake systems on motor vehicles and trailers

Material: EPDM

inside/outside smooth with fabric insert

Bending radius:

approx. 7 x inner diameter

Temperature:

-40°C to +70°C

Operating pressure: 10 bar

Special feature:

Standardized according to DIN 74310:1993

RADIACORD®



Areas of application:

Cooling water hose

Properties:

UV and weather resistant cooling water hose for a wide range of antifreeze

Material: EPDM

inside/outside smooth with fabric insert (from ID 28 outside fabric patterned)

Bending radius:

approx. 10 x inner diameter

Temperature:

-30°C to +100°C

Operating pressure: 6 bar

(from 28 mm inner diameter 4 bar)

Special feature:

Also available in many intermediate dimensions

MILKCORD®/SP



Areas of application:

Food-safe suction and pressure hose for transporting milk and dairy products

Properties:

Due to its flexible design, the hose is often used as a milk tanker hose and for filling and emptying tanks

Material: Rubber

Smooth inside/outside with fabric inserts and steel spiral

Bending Radius:

approx. 6 x inner diameter

Temperature:

-20°C to +90°C

Vacuum: 0.8 bar

Operating pressure: 10 bar

Special feature:

Approved according to European and German food standards

AIRDUC® PUR 355 Food



Areas of application:

Flexible suction hose for grass mowers, embankment mowers and leaf vacuums

Properties:

High abrasion resistant, microbe and hydrolysis resistant

Material: PU

premium polyurethane, smooth inside/corrugated outside, steel spiral

Bending Radius:

1 x Inner diameter

Temperature:

-40°C to +90°C, short-term up to +125°C

Vacuum:

variable depending on diameter

Got everything you need?

We also have the right connectors.

We offer the entire range of high-quality coupling and connection systems for all common hose variants, regardless of whether you use PVC, PU or rubber hoses.

Our wide range of products includes quick couplings, hose fittings, fasteners and other accessories specifically tailored to your needs. Whether you need individual components or complete ready-made sets, we offer you flexible solutions to optimally adapt your hose systems.

The possibility of having our couplings and connection systems already fully assembled saves you time and effort during installation. You can rest assured that your hose systems will work efficiently and reliably.



Product	GEKA® Quick-action coupling	Perrot coupling	Storz coupling	Kamlok coupling
Description	Original quick couplings, lug spacing 40 mm	Coupling for clamps and clamp tray assembly	Forged couplings	Coupling for clamps and clamp tray assembly
Standard	-	-	-	A-A 59326 25.09.98(formerly MIL - C 27487) / EN 14420
Material	Brass gasket: NBR, black	Hot-dip galvanized steel gasket: SBR, black	Aluminum, gasket: NBR, white	Aluminum, stainless steel, brass, polypropylene
Working pressure	10 bar	10 bar	16 bar	3 bar - 16 bar
Execution	Hose fittings, female or male threads and accessories	Incl. hose nozzle, lever locking ring, cup and seal. With fixed levers.	Incl. hose nozzle, female or male thread, as well as accessories	Hose nozzle, female or male thread and accessories

Product	Tanker couplings	Food couplings	Clamping shell	Hose clamps
Description	Coupling for clamps and clamp tray assembly	Coupling for shelving/clamping shell assembly and for pressing	Two-piece clamping shells for the binding of couplings with smooth or combination hose connector and safety collar	Wide belt/screw screw clamps in various sizes and designs
Standard	EN 14420-6	DIN 11851	EN 14420-3	DIN 3017
Material	Brass + Stainless Steel (1.4408)	Stainless Steel (1.4404)	Aluminium and stainless steel	Galvanized steel and stainless steel
Working pressure	16 bar	25 bar - 40 bar	25 bar	-
Execution	Incl. smooth and grooved hose nozzle. Crown ring, clamping ring and lever or curve piece.	Father part including blue food seal, mother part including union nut	Allen screws	One- and two-piece design


You can expect proximity. We're nearby.

With six production facilities in Germany, Italy, Switzerland, North America and China as well as 13 sales, service and warehouse locations we are present around the globe.

Our customers benefit from numerous advantages:

- Globally uniform production quality
- Flexible service for spare parts or original equipment
- Short response times in case of on-site service
- Local contacts for direct support

Our Locations



NORRES Baggerman

- US
- Indiana

- Germany
- Gelsenkirchen
- France
- Cormontreuil
- Netherlands
- Roermond

- Italy
- Cusago
- Inarzo
- Great Britain
- Birmingham
- Romania
- Reghin

- Poland
- Tarnowo Podgórne
- Switzerland
- Balerna
- Czech Republic
- Ostrava
- Hungary
- Felsőzsolca

- China
- Shanghai
- Taiwan
- Taoyua City

- Sales locations
- Production locations



NORRES
BAGGERMAN

Better. Stronger. Together.

Your partner for high-quality hose systems.

NORRES Baggerman Group:

NORRES North America Inc.

701 W Chippewa Ave, Suite 11

South Bend, IN 46614, US

Tel: +1 574 232 9061

Fax: +1 574 232 9091

Email: orders@norres-baggerman.com

www.norres-baggerman.com

NORRES | Baggerman | Agricultural Industry Brochure 07|2024

Liability/copyright: Despite the greatest possible control of the content, no liability is accepted for the completeness and correctness of the content. Technical changes and errors are reserved. Picture credits: ©iStock: fotokostic, courtneyk, stu99, Sergii Petruk, Sjo, todaydesign, baranozdemir ; ©AdobeStock: Atchariya63, TOF, Eva Polikarpova, Stephan Leyk, Dusan Kostic, David A Litman, Kara ; ©Alamy: Jens Schmitz, Jinny Goodman, Rick Dalton - Ag